

CSB1 D13*

- The manual hydraulic raising/lowering function gives the operator greater control and accuracy over their process.
- Built-in water tank provides wet cutting autonomy in isolated locations.
- The lifting eye is located on the machine to simplify loading and transporting.
- Durable high-resistance wheels equipped with sealed heavy-duty bearings ensure a seamless and precise cutting experience.



* Available on request

PRODUCT DATA

Item No.	70184613925	Power source	Diesel
EAN	5450248142829	Motor type	HATZ 1D81 Z
		Power	9.6kW (13 hp)
		Blade x bore	Ø 500 x 25.4mm
		Max. cutting depth	190mm
		Dimensions (L x W x H)	1200 x 600 x 1040mm
		Weight	255kg
		Water tank capacity	40l
		Tool speed RPM	1950min ⁻¹
		Starter	Crank
		Raise and lower	Manual hydraulic
		Propelling	Automatic
		Hand Arm Vibrations	5.08m/s ²
		Sound power / pressure level	114dB(A) /101dB(A)



13 hp



9.6kW




DIESEL

KIT FOR 600MM BLADE GUARD



Item No.	310005876
EAN	5450248129226

PRODUCT FEATURES



MAX CUT DEPTH



BUILT-IN WATER TANK



MANUAL OR HYDRAULIC RAISE
& LOWER THE BLADE



BUILT-IN LIFTING EYE

DIAMOND BLADE RECOMMENDATIONS FOR CSB1 (DIESEL)

Substrate / material	BETON	SILENCIO	ASPHALT	ALL MATERIALS
Recommended product	EXTREME BETON	EXTREME BETON SILENCIO	EXTREME ASPHALT	PRO 4X4 EXPLORER
Diameter	500mm	500mm	500mm	500mm
Bore	25.4mm	25.4mm	25.4mm	25.4mm
Item No.	70184601690	70184630416	70184694913	70184602097
Page reference	33	32	66	52